



UNI SERIES
SENSOR BATTEN

The Uni Sensor Batten features a built-in motion sensor with customisable dimming levels and hold times.

The energy savings the dimmable sensor delivers make this batten the perfect fit for environments with variable occupancy, such as car parks and stairwells. Available in 3 different sizes - 600mm, 1200mm and 1500mm - and IP65 models.

FEATURES

- § Traditional batten profile
- § Sensor with adjustable dim levels & hold times
- § Surface mountable or suspendable
- § No external junction box required
- § Tri-colour

SENSOR DEFAULT SETTINGS

HOLD TIME	10mins	STANDBY PERIOD	5mins
DAYLIGHT SENSOR	50Lux	STANDBY LEVEL	10%

SPECIFICATIONS

POWER FACTOR	>0.9
CRI	>80
BEAM ANGLE	1200
SENSOR RANGE	10 metres
IP RATING	20 or 65
LIFETIME (L70)	>60,000hrs
WARRANTY	5 years

LPM = LCP LOW POWER MODE

MODEL NUMBER	CCT	LENGTH	WATT	LCP	LPM	LUMENS	EFFICACY	IP
EP-UNI-TS620-18	4/5/6000K	600mm	18	EP-	18.3	1.8	2160	120lm/W 20
UNI-TS1220-25	4/5/6000K	1200mm	25	EP-	24.5	2.5	3000	120lm/W 20
UNI-TS1220-35	4/5/6000K	1200mm	35	EP-	34.5	3.5	4200	120lm/W 20
UNI-TS1220-45	4/5/6000K	1200mm	45	EP-	44.5	4.5	5400	120lm/W 20
UNI-TS1520-45	4/5/6000K	1500mm	45	EP-	44.5	4.5	5400	120lm/W 20
UNI-TS665-18	4/5/6000K	600mm	18	EP-UNI-	18.3	1.8	2160	120lm/W 65
TS1265-25	4/5/6000K	1200mm	25	EP-UNI-	24.5	2.5	3000	120lm/W 65
TS1265-35	4/5/6000K	1200mm	35		34.5	3.5	4200	120lm/W 65

Available now Made to order, 8-10 week lead time

VEET Approved VIC	ESS Approved NSW	EEIS Approved ACT	REES Approved SA	SAA	NATA	RCM
-------------------------	------------------------	-------------------------	------------------------	-----	------	-----